

SECTION 1: Product identifier

1.1. GHS Product identifier

Product form : Mixture
Product name : Sani-Vak G3
Product code : Formula: LB-VAKG3/1
Part No: (E)SP-VAKG3 series

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Cleaning agent
Industrial use
Restrictions on use : None known

1.4. Details of manufacturer or importer

Manufacturer

Celeste Industries Corporation
8007 Industrial Park Road
Easton, Maryland 21601 USA
T 1-410-822-5775
info@celestecorp.com - www.celestecorp.com

Distributor

Boeing Distribution Australia Pty Ltd
20-22 Lindaway Place Tullamarine, Vic 3043
T 61-3-9339-3000 / 61-3-9338-9773
prc@boeing.com

1.5. Emergency phone number

Emergency number : For Chemical Emergency, Spill, Leak, Fire, Exposure or Accident call CHEMTREC (24 hours) within USA and CANADA: 1-800-424-9300;
Outside USA and Canada (collect call accepted): 1-703-527-3883


SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

| | |
|---|------|
| Corrosive to metals, Category 1 | H290 |
| Skin corrosion/irritation, Category 1C | H314 |
| Serious eye damage/eye irritation, Category 1 | H318 |

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) : 
GHS05
Corrosion

Signal word (GHS AU) : Danger

Contains : Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-hydroxy-, mono-C8-10-alkyl ethers, phosphates (0.5 - 1.5 %); Sodium 1-octanesulfonate (0.5 - 1.5 %); Benzenesulfonic acid, C10-16-alkyl derivatives (0.1 - 1 %)

Hazard statements (GHS AU) : H290 - May be corrosive to metals
H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS AU) : P234 - Keep only in original container.
P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

Sani-Vak G3

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

protection.

P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water .

P363 - Wash contaminated clothing before reuse.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor.

P390 - Absorb spillage to prevent material damage.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

| Name | CAS-No. | % |
|---|-------------|-----------|
| Malic acid | 6915-15-7 | 1 - 5 |
| Citric acid | 77-92-9 | 1 - 5 |
| Sulfamic acid | 5329-14-6 | 1 - 5 |
| Sodium xylenesulfonate | 1300-72-7 | 0.5 - 1.5 |
| Sodium 1-octanesulfonate | 5324-84-5 | 0.5 - 1.5 |
| Poly(oxy-1,2-ethanediyl), .alpha.-hydro.-omega.-hydroxy-, mono-C8-10-alkyl ethers, phosphates | 68130-47-2 | 0.5 - 1.5 |
| Benzenesulfonic acid, C10-16-alkyl derivatives | 68584-22-5 | 0.1 - 1 |
| Non hazardous or chemicals not contributing to classification | Proprietary | To 100% |

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

| | |
|---------------------------------------|---|
| First-aid measures after inhalation | : If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. |
| First-aid measures after skin contact | : If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTER or doctor. |
| First-aid measures after eye contact | : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. |
| First-aid measures after ingestion | : IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor. Never give anything by mouth to an unconscious person. |

4.2. Symptoms caused by exposure

| | |
|-------------------------------------|---|
| Symptoms/effects after inhalation | : Causes burns to the respiratory system. |
| Symptoms/effects after skin contact | : Causes severe skin burns. Symptoms may include redness, pain, blisters. |
| Symptoms/effects after eye contact | : Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns. |
| Symptoms/effects after ingestion | : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. |

4.3. Medical attention and special treatment

| | |
|-----------------------------------|--|
| Other medical advice or treatment | : Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). |
|-----------------------------------|--|

Sani-Vak G3

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).
Unsuitable extinguishing media : Do not use water jet.

5.2. Specific hazards arising from the chemical

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon. Irritating fumes. Oxides of sodium.
General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.1.1. For non-emergency personnel

- Emergency procedures : Do not touch or walk on the spilled product.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and materials for containment and cleaning up

- For containment : Stop leak if safe to do so. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
Methods for cleaning up : Absorb spillage to prevent material damage. Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : May be corrosive to metals.
Precautions for safe handling : Do not get in eyes, on skin, or on clothing. Do not breathe dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Provide adequate ventilation.
Hygiene measures : Take off immediately all contaminated clothing and wash it before reuse. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store in a dry, cool and well-ventilated place. Keep only in original container. Keep out of direct sunlight. Store in corrosive resistant container with a resistant inner liner. Store locked up.

Sani-Vak G3

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

No additional information available

8.2. Biological Monitoring

No additional information available

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Wear suitable gloves resistant to chemical penetration. Consult glove manufacturer's product information on material suitability and material thickness.

Eye protection : Wear eye/face protection

Skin and body protection : Wear suitable protective clothing

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

Environmental exposure controls : Avoid release to the environment.

Other information : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

Physical state : Liquid

Appearance : No data available

Colour : Amber

Odour : No data available

Odour threshold : No data available

pH : 1.5 – 2.5

pH solution : No data available

Relative evaporation rate (butylacetate=1) : No data available

Melting point / Freezing point : Melting point: 32 °F (0 °C)

Boiling point : ≈ 212 °F (≈100 °C)

Flash point : No data available

Auto-ignition temperature : No data available

Flammability : No data available

Vapour pressure : No data available

Relative density : No data available

Density : Relative density: 1 – 1.1

Solubility : Soluble in water.

Partition coefficient n-octanol/water : No data available

Explosive properties : Not explosive.

Oxidising properties : Not oxidizing

Explosive limits : No data available

Minimum ignition energy : No data available

Fat solubility : No data available

SECTION 10: Stability and reactivity

Reactivity : No dangerous reactions known under normal conditions of use. May be corrosive to metals.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No dangerous reactions known under normal conditions of use.

Sani-Vak G3

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

| | |
|----------------------------------|--|
| Conditions to avoid | : Heat. Do not mix with other chemicals. Incompatible materials. |
| Incompatible materials | : Aluminium. Strong oxidizing agents. Strong bases. |
| Hazardous decomposition products | : May include, and are not limited to: oxides of carbon. Irritating fumes. Oxides of sodium. |

SECTION 11: Toxicological information

| | |
|-----------------------------|-------------------|
| Acute toxicity (oral) | : Not classified. |
| Acute toxicity (dermal) | : Not classified. |
| Acute toxicity (inhalation) | : Not classified. |

Sodium xylenesulfonate (1300-72-7)

| | |
|--------------------|---|
| LD50 oral rat | ≥ 3346 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), 95% CL: 3196 - 3503 |
| LD50 dermal rabbit | ≥ 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity) |

Benzenesulfonic acid, C10-16-alkyl derivatives (68584-22-5)

| | |
|---------------------|---|
| LD50 oral rat | 775 mg/kg (Source: CHEMVIEW) |
| LD50 dermal rabbit | 2000 mg/kg (Source: CHEMVIEW) |
| LC50 inhalation rat | > 1.9 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity) |

Malic acid (6915-15-7)

| | |
|---------------------|---|
| LD50 oral rat | 3500 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity) |
| LD50 dermal rabbit | > 20000 mg/kg bodyweight Animal: rabbit |
| LC50 inhalation rat | > 1.306 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)) |

Sulfamic acid (5329-14-6)

| | |
|-----------------|--|
| LD50 oral rat | 2140 mg/kg bodyweight Animal: rat, Animal sex: female |
| LD50 dermal rat | > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity) |

Citric acid (77-92-9)

| | |
|-----------------|---|
| LD50 oral rat | 3 g/kg (Source: NLM_CIP) |
| LD50 oral | 5400 mg/kg bodyweight Animal: mouse, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Remarks on results: other., 95% CL: 4500 - 6400 |
| LD50 dermal rat | > 2000 mg/kg (Source: EU_CLH) |

Skin corrosion/irritation : Causes severe skin burns.
pH: 1.5 – 2.5
Based on Corrositex data (OECD TG435)

Serious eye damage/irritation : Causes serious eye damage.
pH: 1.5 – 2.5
Based on Corrositex data (OECD TG435)

Respiratory or skin sensitisation : Not classified.

Germ cell mutagenicity : Not classified.

Carcinogenicity : Not classified.

Sodium xylenesulfonate (1300-72-7)

| | |
|---|--|
| NOAEL (chronic, oral, animal/female, 2 years) | ≥ 60 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Remarks on results: other: |
|---|--|

Reproductive toxicity : Not classified.

Sulfamic acid (5329-14-6)

| | |
|---------------------------|--|
| NOAEL (animal/female, F1) | 500 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OPP 83-4 (Reproduction and Fertility Effects) |
|---------------------------|--|

Sani-Vak G3

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

STOT-single exposure : Not classified.

Citric acid (77-92-9)

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified.

Sodium xylenesulfonate (1300-72-7)

NOAEL (oral, rat, 90 days) : 763 – 3534 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Sodium 1-octanesulfonate (5324-84-5)

NOAEL (oral, rat, 90 days) : > 430 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

Benzenesulfonic acid, C10-16-alkyl derivatives (68584-22-5)

NOAEL (oral, rat, 90 days) : 500 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)

NOAEL (dermal, rat/rabbit, 90 days) : > 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Citric acid (77-92-9)

LOAEL (oral, rat, 90 days) : 8000 mg/kg bodyweight Animal: rat

NOAEL (oral, rat, 90 days) : 4000 mg/kg bodyweight Animal: rat

Aspiration hazard : Not classified.

Sodium xylenesulfonate (1300-72-7)

Animal studies and expert judgment for classification : False

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-hydroxy-, mono-C8-10-alkyl ethers, phosphates (68130-47-2)

Animal studies and expert judgment for classification : False

Sodium 1-octanesulfonate (5324-84-5)

Animal studies and expert judgment for classification : False

Benzenesulfonic acid, C10-16-alkyl derivatives (68584-22-5)

Animal studies and expert judgment for classification : False

Malic acid (6915-15-7)

Animal studies and expert judgment for classification : False

Sulfamic acid (5329-14-6)

Animal studies and expert judgment for classification : False

Citric acid (77-92-9)

Animal studies and expert judgment for classification : False

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified.

Hazardous to the aquatic environment, long-term (chronic) : Not classified.

Sani-Vak G3

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Other information : No other effects known.

| Sodium xylenesulfonate (1300-72-7) | |
|---|--|
| LC50 - Fish [1] | ≥ 1580 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) |
| EC50 - Crustacea [1] | > 1020 mg/l Test organisms (species): Daphnia magna |
| Partition coefficient n-octanol/water | -3.12 (at 20 °C (at pH 11.96)) |

| Sodium 1-octanesulfonate (5324-84-5) | |
|---|---|
| LC50 - Fish [1] | > 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) |
| EC50 - Crustacea [1] | 421 mg/l Test organisms (species): Daphnia magna |

| Benzenesulfonic acid, C10-16-alkyl derivatives (68584-22-5) | |
|--|---|
| LC50 - Fish [1] | 3 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: IUCLID) |
| EC50 - Crustacea [1] | 2.9 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| Partition coefficient n-octanol/water | 2 (at 23 °C) |

| Malic acid (6915-15-7) | |
|-------------------------------|---|
| LC50 - Fish [1] | > 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) |

| Sulfamic acid (5329-14-6) | |
|----------------------------------|---|
| LC50 - Fish [1] | 70.3 mg/l Test organisms (species): Pimephales promelas |
| EC50 - Crustacea [1] | 71.6 mg/l Test organisms (species): Daphnia magna |
| LOEC (chronic) | 34 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC (chronic) | 19 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC chronic fish | ≥ 60 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '34 d' |

| Citric acid (77-92-9) | |
|---------------------------------------|--|
| LC50 - Fish [1] | 1516 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus Source: OECD_SIDS) |
| EC50 - Other aquatic organisms [1] | > 50 mg/l Test organisms (species): other aquatic crustacea: |
| Partition coefficient n-octanol/water | -1.72 (at 20 °C) |

12.2. Persistence and degradability

| Sani-Vak G3 | |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |

12.3. Bioaccumulative potential

| Sani-Vak G3 | |
|---------------------------|------------------|
| Bioaccumulative potential | Not established. |

| Sodium xylenesulfonate (1300-72-7) | |
|---|--------------------------------|
| Partition coefficient n-octanol/water | -3.12 (at 20 °C (at pH 11.96)) |

| Benzenesulfonic acid, C10-16-alkyl derivatives (68584-22-5) | |
|--|--------------|
| Partition coefficient n-octanol/water | 2 (at 23 °C) |

| Citric acid (77-92-9) | |
|---------------------------------------|------------------|
| Partition coefficient n-octanol/water | -1.72 (at 20 °C) |

Sani-Vak G3

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

12.4. Mobility in soil

| Sodium xylenesulfonate (1300-72-7) | |
|---|--------------------------------|
| Partition coefficient n-octanol/water | -3.12 (at 20 °C (at pH 11.96)) |
| Benzenesulfonic acid, C10-16-alkyl derivatives (68584-22-5) | |
| Partition coefficient n-octanol/water | 2 (at 23 °C) |
| Citric acid (77-92-9) | |
| Partition coefficient n-octanol/water | -1.72 (at 20 °C) |

12.5. Other adverse effects

| | |
|-----------------------|---------------------------------------|
| Ozone | : Not classified. |
| Other adverse effects | : No additional information available |

| Sani-Vak G3 | |
|--|-------|
| Fluorinated greenhouse gases | False |
| Sodium xylenesulfonate (1300-72-7) | |
| Fluorinated greenhouse gases | False |
| Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-hydroxy-, mono-C8-10-alkyl ethers, phosphates (68130-47-2) | |
| Fluorinated greenhouse gases | False |
| Sodium 1-octanesulfonate (5324-84-5) | |
| Fluorinated greenhouse gases | False |
| Benzenesulfonic acid, C10-16-alkyl derivatives (68584-22-5) | |
| Fluorinated greenhouse gases | False |
| Malic acid (6915-15-7) | |
| Fluorinated greenhouse gases | False |
| Sulfamic acid (5329-14-6) | |
| Fluorinated greenhouse gases | False |
| Citric acid (77-92-9) | |
| Fluorinated greenhouse gases | False |

SECTION 13: Disposal considerations

| | |
|--|---|
| Product/Packaging disposal recommendations | : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. |
|--|---|

SECTION 14: Transport information

14.1. UN number

| | |
|---------------|--------|
| UN-No. (ADG) | : 1760 |
| UN-No. (IMDG) | : 1760 |
| UN-No. (IATA) | : 1760 |

14.2. UN Proper Shipping Name

| | |
|-----------------------------|--|
| Proper Shipping Name (ADG) | : CORROSIVE LIQUID, N.O.S. (C8-10 Alkyl alcohol ethoxylate, phosphate ester, Sodium 1-octanesulfonate) |
| Proper Shipping Name (IMDG) | : CORROSIVE LIQUID, N.O.S. (C8-10 Alkyl alcohol ethoxylate, phosphate ester, Sodium 1-octanesulfonate) |

Sani-Vak G3

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Proper Shipping Name (IATA) : Corrosive liquid, n.o.s (C8-10 Alkyl alcohol ethoxylate, phosphate ester, Sodium 1-octanesulfonate)

14.3. Transport hazard class(es)

ADG

Transport hazard class(es) (ADG) : 8
Danger labels (ADG) : 8



IMDG

Transport hazard class(es) (IMDG) : 8
Danger labels (IMDG) : 8



IATA

Transport hazard class(es) (IATA) : 8
Danger labels (IATA) : 8



14.4. Packing group

Packing group (ADG) : III - Substances presenting low danger
Packing group (IMDG) : III
Packing group (IATA) : III

14.5. Environmental hazards

Marine pollutant : No
Dangerous for the environment : No
Other information : No supplementary information available.

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available.
Special transport precautions : Do not handle until all safety precautions have been read and understood.

Transport by road and rail

UN-No. (ADG) : 1760
Special provision (ADG) : 223, 274
Limited quantities (ADG) : 5I
Excepted quantities (ADG) : E1
Packing instructions (ADG) : P001, IBC03, LP01
Portable tank and bulk container instructions (ADG) : T7
Portable tank and bulk container special provisions (ADG) : TP1, TP28

Transport by sea

UN-No. (IMDG) : 1760

Sani-Vak G3

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Air transport

UN-No. (IATA) : 1760

14.8. Hazchem or Emergency Action Code

Hazchem Code : 2X

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

15.2. International agreements

No additional information available

SECTION 16: Other information

Revision date : 20/06/2024
Expiry date : 20/06/2029
Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



Classification

| | |
|---------------|------|
| Met. Corr. 1 | H290 |
| Skin Corr. 1C | H314 |
| Eye Dam. 1 | H318 |

Full text of H-statements

| | |
|-----------------------|--|
| Acute Tox. 4 (Dermal) | Acute toxicity (dermal), Category 4 |
| Acute Tox. 4 (Oral) | Acute toxicity (oral), Category 4 |
| Eye Dam. 1 | Serious eye damage/eye irritation, Category 1 |
| Eye Irrit. 2A | Serious eye damage/eye irritation, Category 2A |
| Met. Corr. 1 | Corrosive to metals, Category 1 |
| Skin Corr. 1A | Skin corrosion/irritation, Category 1A |
| Skin Corr. 1B | Skin corrosion/irritation, Category 1B |
| Skin Corr. 1C | Skin corrosion/irritation, Category 1C |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 |
| STOT SE 3 | Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation |
| H290 | May be corrosive to metals |
| H302 | Harmful if swallowed |
| H312 | Harmful in contact with skin |
| H314 | Causes severe skin burns and eye damage |
| H315 | Causes skin irritation |
| H318 | Causes serious eye damage |
| H319 | Causes serious eye irritation |

Sani-Vak G3

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Full text of H-statements

| | |
|------|----------------------------------|
| H335 | May cause respiratory irritation |
|------|----------------------------------|

Safety Data Sheet (SDS), Australia - Nexreg 2022

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.